

# Eclipse

- User-friendly (stand-alone and remote)
- Dependable and reliable
- All popular I/O formats are supported
- Powerful data editing tools
- Supplied DOS and Windows\* remote control software
- Ultra-fast programming
- Customer RAM expansion using SIMMs
- Ideal for production and development

Stag's Eclipse is the universal programmer that is guaranteed to take you into the next millennium.

Expanding the system to meet future needs is simply a matter of adding low-cost pin-driver boards (16 pin-drivers/board), extra RAM in the form of SIMMs and optional package modules. Eclipse can have up to 256 pin-drivers installed within the original unit, and if that isn't enough, Stag's proprietor Scalable Architecture is further expandable to encompass any foreseeable future demands.

All types of device security are implemented. A full programming sequence can be defined to fit the operator's requirements.

When used in stand-alone mode, Eclipse will sometimes need to be connected to peripheral equipment - maybe to print a file or download data. This is easily achieved through either its high speed serial port (baud rates to 115K) or Centronics parallel port. Connection for data transfer is possible from most major computer platforms as Eclipse supports standard handshaking protocols. So if you have a PC, VAX\*, Sun workstation or other industry-standard computer, Eclipse won't leave you in the dark.

During the past decade, PCs and workstations have become standard equipment for the professional design engineer. Obvi-



ously, in today's high-pressure environment, to have a device programmer on-line at all times would be ideal. However, there are still areas where a stand-alone programmer is required. To address this double requirement, Stag has provided Eclipse with dual access capability, making it the world's first universal programmer to be equally at home under local or computer remote control - and with full functionality in both areas. Remote operation is via a direct link from your PC using the supplied communication software which can be run as a true Windows application or as a DOS program providing a Windows-style environment.

#### INTEL FLASH MEMORY SUPPORTED:

28F010, 28F001BX, 28F020, 28F002BC, 28F002BL, 28F002BV, 28F002BX, 28F200BL, 28F200BV, 28F200BX, 28F200CV, 28F004BE, 28F004BL, 28F004BV, 28F004BX, 28F004SC, 28F400BL, 28F400BV, 28F400BX, 28F400CE, 28F400CV, 28F008BE, 28F008BV, 28F008SA, 28F008SC, 28F800BV, 28F800CE, 28F800CV, 28F016SA, 28F016SC, 28F016SV, 28F016XD, 28F016XS, 28F032SA

#### AVAILABILITY:

Now

#### CONTACT:

Stag Devices Inc.  
130 Capital Drive  
Golden, CO 80401  
Phone: (303) 279-6868  
FAX: (303) 279-6869

